

# SUSTAINABLE AUTOMATION, LLC

## SECONDARY LOAD CONTROLLER FOR 3-PHASE 480V HOT WATER BOILER APPLICATIONS

### STANDARD MODELS

#### 20" SERIES VWBG BOILER

MODEL	RESOLUTION (KW)	MAXIMUM ELEMENT SIZE (KW)	BINARY STEPS	LINEAR STEPS	TOTAL CAPACITY (KW)
SLC-HW-70-2.25-480-60	2.25	9	5	0	69.75
SLC-HW-106-2.25-480-60	2.25	9	4	2	105.75
SLC-HW-142-2.25-480-60	2.25	9	4	3	141.75
SLC-HW-178-2.25-480-60	2.25	9	4	4	177.75
SLC-HW-214-2.25-480-60	2.25	9	4	5	213.75
SLC-HW-70-2.5-480-60	2.5	10	5	0	77.5
SLC-HW-118-2.5-480-60	2.5	10	4	2	117.5
SLC-HW-158-2.5-480-60	2.5	10	4	3	157.5
SLC-HW-198-2.5-480-60	2.5	10	4	4	197.5
SLC-HW-238-2.5-480-60	2.5	10	4	5	237.5
SLC-HW-104-4.5-480-60	4.5	9	3	2	103.5
SLC-HW-140-4.5-480-60	4.5	9	3	3	139.5
SLC-HW-176-4.5-480-60	4.5	9	3	4	175.5
SLC-HW-212-4.5-480-60	4.5	9	3	5	211.5
SLC-HW-115-5-480-60	5	10	3	2	115
SLC-HW-155-5-480-60	5	10	3	3	155
SLC-HW-195-5-480-60	5	10	3	4	195
SLC-HW-235-5-480-60	5	10	3	5	235

#### Notes:

1. All models use a double-door floor mount NEMA-12 enclosure measuring 72"H x 48"W x 10"D, except models that are shaded in the chart, which use a double-door enclosure measuring 72"H x 60"W x 10"D.
2. Higher power units are available using 30" or 42" diameter boilers.

Rev. 1, 12/2003